

# Permo® light Permo® light SK<sup>2</sup>



Permo® light is a strong 3-layer vapour permeable roofing underlay suitable for warm and cold pitched roofs.

### Installation

Permo® light should be laid in accordance with our installation details and BBA/IAB Certificates.

Permo® light SK<sup>2</sup> has a double integral tape at the laps. This creates a very effective and secure airtight seal, reducing energy loss.

- Glue-on-glue connection creates perfect seal
- Problems laying in wet/dusty conditions avoided because both strips protected by release paper

### Technical data

Thickness	0.5 mm
Weight	145 g/m <sup>2</sup>
Water vapour resistance BS 3177	0.18 MNs/g
Water vapour transmission BS3177	1149 g/m <sup>2</sup> /day
Water column	> 2 m
Tensile strength longitudinal, BS 2782-3	264 N/5cm
Tensile strength transverse, BS 2782-3	210 N/5cm
Nail tear strength longitudinal, MOAT 27:5.4.1	116 N
Nail tear strength transverse, MOAT 27:5.4.1	96 N
<b>Additional technical data</b>	<b>CE</b>
Fire Rating	E
Temperature	-40°C to + 80°C
UV exposure	4 months

### BBA

# KLOBER

### Product features & benefits

- Robust vapour permeable underlay
- 3 layer material with grid
- BBA, IAB & CE approved for cold & warm roofs
- UV stable for 4 months
- Hydrophobically treated
- Allows the roof structure to breathe, yet fully waterproof
- Counterbattens only required on fully supported applications
- Limits air leakage in a sealed roof application
- Type LR underlay
- Permo light SK<sup>2</sup> has a double integral tape - creating a strong & durable airtight seal to reduce energy loss. This avoids the use of a separate tape, making installation faster.

### Area of application

Suitable for cold and warm roofs

### Material

Permo® light is a strong laminated sheet material, with outer layers of polypropylene, and an inner layer of microporous polyethylene film

### Colour

Grey

### Roll sizes

50 x 1.5m (75m<sup>2</sup>)  
50 x 1.1m (55m<sup>2</sup>)

### Roll weights

11 kg  
8.5 kg

### Packaging (per pallet)

20 rolls

### Product codes

50 x 1.5m KU0043-1  
50 x 1.1m KU0043-05-0400

### Permo® light SK<sup>2</sup>

50 x 1.5m KU0043-11  
For 50 x 1.1m please contact the sales office

### Certifications

CE certified



### Related products

- Underlay Support Trays
- Adhesive tapes for joining vertical laps & repairs
- Eaves closers for counterbattened roofs